


FAST CONNECTOR**SINGLE MODE APC FAST CONNECTOR**

For SC/APC Product Code: FO-0302SMA353Q

For SC/UPC Product Code: FO-0302SMU353Q

APPLICATIONS


CATV, CCTV, FTTX, FTTH, Telecommunication Networks,
 Active Device Termination, Local Area Networks (LANs),
 Video, Data Processing Networks
 Wide Area Networks(WANs)
 Premise Installations
 Industrial and Medical

**DATASHEET**

ITEMS	TEST CONDITION	VALUE
OPTICAL PERFORMANCE	Insertion Loss (1310nm&1550nm)	<0.2dB(typical) /0.3dB (Max)
	Return Loss (1310nm&1550nm)	UPC \geq -50 dB - APC \geq -60 dB
Environmental Performance (Max. Insertion Loss Change)	Temperature cycle -40 ° ~ +75 ° (96 hours)	<0.3dB
Mechanical Performance (Max. Insertion Loss Change)	Online tension 20N- 10N	<0.3dB
	Impaction3 axis/3times 4m high	<0.3dB
	Repeated operation times	5

FAST CONNECTOR

General Features				
Connector Type	SC (PC or UPC)	LC (PC or UPC)	SC/APC	LC/APC
Insertion Loss	0,2 dB	0,2 dB	0,2 dB	0,1 dB
Reflection Loss	≥ -50 dB	≥ -50 dB	≥ - 60 dB	≥ -60 dB
Operating Temperture	-40°C / +75°C	-40°C / +75°C	-40°C / +75°C	-40°C / +75°C
Storage Temperture	-40°C / +85°C	-40°C / +85°C	-40°C / +85°C	-40°C / +85°C
Ferrule	Zirconia Ceramic	Zirconia Ceramic	Zirconia Ceramic	Zirconia Ceramic
Alignment Sleeve	Zirconia Ceramic	Zirconia Ceramic	Zirconia Ceramic	Zirconia Ceramic
Flame Retardent	UL – 94 V-O			
Durability	Mating cycles > 1000			
Color	Blue	Blue	Green	Green

Surface Geometric Features

Specifications	Value Provided
Radius Of Curvature(R) mm	10
Apex Offset (AO) µm	0
Spherical Fiber Height (SpH) nm	-50 =< SpH =< 50